

Bosch 32C Manifold Specifications		Wall Mount			
Part Number	WBCC2NGSK / WBCC2LP5SK	WBCC3NGSK / WBCC3LP5SK	WBCC4NGSK / WBCC4LP5SK	WBCC5NGSK / WBCC5LP5SK	WBCC6NGSK / WBCC6LP5SK
Part Number (50 degree limited)	WBCC2NG5SK / WBCC2LP5SK	WBCC3NG5SK / WBCC3LP5SK	WBCC4NG5SK / WBCC4LP5SK	WBCC5NG5SK / WBCC5LP5SK	WBCC6NG5SK / WBCC6LP5SK
Installation	Internal* or External^	Internal* or External^	Internal* or External^	Internal* or External^	Internal* or External^
Ignition	Electronic	Electronic	Electronic	Electronic	Electronic
L/min (25°C rise)	64	96	128	160	192
Min. operating inlet water pressure (kPa)	200	200	200	200	200
Max. inlet water pressure (kPa)	950	950	950	950	950
Mj/H	434	651	868	1085	1302
Temperature Range	The appliance BC3200RA is preset to 55°C and can be adjusted by connecting the connector of the harness to 50°C, 75°C and 85°C. And it can be adjusted by programming the CPU on the PCB to 40°C, 60°C and 65°C. BC3200RA5 is preset to 50°C and can be adjusted by connecting the connector or programming the CPU on the PCB to 40°C and 42°C. These appliances offer two types of remote controllers as optional accessories. When a remote controller is connected, BC3200RA allows settings from 37°C - 48°C in 1°C steps plus seven additional settings of 50°C, 55°C, 60°C, 65°C, 70°C, 75°C and 80°C.				
Min. Flow (L/min)	3.5	3.5	3.5	3.5	3.5
Min. constant water pressure for Max. flow (kPa)	200	200	200	200	200
Star rating (Thermal Efficiency)	6 stars (94%)	6 stars (94%)	6 stars (94%)	6 stars (94%)	6 stars (94%)
Antifrost	Yes	Yes	Yes	Yes	Yes
Gas Type	NG/LPG	NG/LPG	NG/LPG	NG/LPG	NG/LPG
Crate Height x Width x Depth (mm)	300 x 1100 x 1100	300 x 1500 x 1100	300 x 1100 x 1100 (x2)	300 x 1100 x 1100 300 x 1500 x 1100	300 x 1500 x 1100 (x2)
Combined carton weight (Kg)	110	154	220	264	308
Parts and Labour Warranty	2 Years	2 Years	2 Years	2 Years	2 Years
Heat Exchanger Warranty (part only)	5 Years	5 Years	5 Years	5 Years	5 Years
Pipe Connection Size	40mm	40mm	40mm	40mm	40mm
Controller required	RCM3211	RCM3211	RCM3211	RCM3211	RCM3211
Quick Connection Cable required	Yes [KMQC0703339]	No	No	No	No
System Controller required	No	Yes [KMSC201]	Yes [KMSC201]	Yes [KMSC201]	Yes [KMSC201]
Cable for system controller	No	Yes [0700073 x 2]	Yes [0700073 x 3]	Yes [0700073 x 4]	Yes [0700073 x 5]
Manifold pack dimensions (Height x Width x Depth) mm	1540 x 993 x 286	1540 x 1468 x 286	Combination of 2 x WBCC2	Combination of 1 x WBCC2 & 1 x WBCC3	Combination of 2 x WBCC3

\*Flueing required – supplied exclusively from Bosch

^ External vent cap required [BCVC-100C]

Bosch 32C Manifold Specifications		Floor Mount			
Part Number	FBCC2NGSK / FBCC2LP5SK	FBCC3NGSK / FBCC3LP5SK	FBCC4NGSK / FBCC4LP5SK	FBCC5NGSK / FBCC5LP5SK	FBCC6NGSK / FBCC6LP5SK
Part Number (50 degree limited)	FBCC2NG5SK / FBCC2LP5SK	FBCC3NG5SK / FBCC3LP5SK	FBCC4NG5SK / FBCC4LP5SK	FBCC5NG5SK / FBCC5LP5SK	FBCC6NG5SK / FBCC6LP5SK
Installation	Internal* or External^	Internal* or External^	Internal* or External^	Internal* or External^	Internal* or External^
Ignition	Electronic	Electronic	Electronic	Electronic	Electronic
L/min (25°C rise)	64	96	128	160	192
Min. operating inlet water pressure (kPa)	200	200	200	200	200
Max. inlet water pressure (kPa)	950	950	950	950	950
Mj/H	434	651	868	1085	1302
Temperature Range	The appliance BC3200RA is preset to 55°C and can be adjusted by connecting the connector of the harness to 50°C, 75°C and 85°C. And it can be adjusted by programming the CPU on the PCB to 40°C, 60°C and 65°C. BC3200RA5 is preset to 50°C and can be adjusted by connecting the connector or programming the CPU on the PCB to 40°C and 42°C. These appliances offer two types of remote controllers as optional accessories. When a remote controller is connected, BC3200RA allows settings from 37°C - 48°C in 1°C steps plus seven additional settings of 50°C, 55°C, 60°C, 65°C, 70°C, 75°C and 80°C.				
Min. Flow (L/min)	3.5	3.5	3.5	3.5	3.5
Min. constant water pressure for Max. flow (kPa)	200	200	200	200	200
Star rating (Thermal Efficiency)	6 stars (94%)	6 stars (94%)	6 stars (94%)	6 stars (94%)	6 stars (94%)
Antifrost	Yes	Yes	Yes	Yes	Yes
Gas Type	NG/LPG	NG/LPG	NG/LPG	NG/LPG	NG/LPG
Crate Height x Width x Depth (mm)	300 x 1100 x 1100	300 x 1500 x 1100	300 x 1100 x 1100 (x2)	300 x 1100 x 1100 300 x 1500 x 1100	300 x 1500 x 1100 (x2)
Combined carton weight (Kg)	110	154	220	264	308
Parts and Labour Warranty	2 Years	2 Years	2 Years	2 Years	2 Years
Heat Exchanger Warranty (part only)	5 Years	5 Years	5 Years	5 Years	5 Years
Pipe Connection Size	40mm	40mm	40mm	40mm	40mm
Controller required	RCM3211	RCM3211	RCM3211	RCM3211	RCM3211
Quick Connection Cable required	Yes [KMQC0703339]	No	No	No	No
System Controller required	No	Yes [KMSC201]	Yes [KMSC201]	Yes [KMSC201]	Yes [KMSC201]
Cable for system controller	No	Yes [0700073 x 2]	Yes [0700073 x 3]	Yes [0700073 x 4]	Yes [0700073 x 5]
Manifold pack dimensions (Height x Width x Depth) mm	1540 x 993 x 286	1540 x 1468 x 286	Combination of 2 x WBCC2	Combination of 1 x WBCC2 & 1 x WBCC3	Combination of 2 x WBCC3

\*Flueing required – supplied exclusively from Bosch

^ External vent cap required [BCVC-100C]